



产品技术参数 PRODUCT TECHNICAL PARAMETERS

● 5~10mA系列高压二极管 SERIES HV DIODES

型号 Type	反向重复 峰值电压 Repetitive Peak Reverse Voltage V_{RRM} (KV)	正向平 均电流 Avg. Forward Current $I_{F(AV)}$ (mA)	最大浪 涌电流 Maximum surge current I_{FSM} (A)	正向峰 值电压 Peak Forward Voltage V_{FM} (V)	反向峰 值电流 Peak reverse current I_{RRM1} I_{RRM2} (μ A)		反向恢 复时间 Reverse Recovery Time T_{rr} (ns)	负极 标记 Cathode mark	图号 Drawing No.
NV04	4	5	0.5	18	2	5	100		1-1
JB04	4	5	0.5	18	2	5	100		1-2
JB08	8	5	0.5	25	2	5	100	^	1-2
2CL4	4	5	0.5	18	2	5	100		3
2CL6	6	5	0.5	20	2	5	100		3
2CL8	8	5	0.5	25	2	5	100	^	3
2CL10	10	5	0.5	30	2	5	100		3
2CL12	12	5	0.5	35	2	5	100		3
2CL69	4	5	0.5	18	2	5	100		2-1
2CL70	6	5	0.5	20	2	5	100		2-1
2CL71	8	5	0.5	25	2	5	100	^	2-1
2CL72	10	5	0.5	30	2	5	100		2-2
2CL73	12	5	0.5	35	2	5	100		2-2
2CL74	14	5	0.5	40	2	5	100		2-2
2CL75	16	5	0.5	43	2	5	100		2-3
2CL76	18	5	0.5	45	2	5	100		2-3
2CL77	20	5	0.5	45	2	5	100		2-3
2CL79	25	10	0.5	50	2	5	100		2-3
2CL82	30	10	0.5	55	2	5	100		2-3

