

### WIRE SPECIFICATION

规格型号 SPEC NO.	UL3239 20AWG	参照标准 REFERENCE STANDARD	UL1581/758
额定温度 RATED TEMPERATURE	150℃	额定电压 RATED VOLTAGE	20KV-DC
阻燃等级 FLAME RETARDANT GRADE	VW-1	环保标准 ENVIRONMENTAL STANDARDS	RoHS

#### 结构项目 CONSTRUCTION ITEM

导体 CONDUCTOR	构造规格 SECTIONAL AREA	AWG/ mm	21/0.178±0.008TS
	导体材质 MATERIAL	.....	Tinned copper
	截面积 SECTIONAL AREA	mm <sup>2</sup>	0.52
	绞合外径 STRANDED DIAMETER	mm	0.94
绝缘 INSULATION	材质 MATERIAL	.....	Silicone
	平均厚度 THE AVERAGE THICKNESS	mm	1.29
	最小厚度 MINIMUM GAUGE	mm	1.1
	颜色 COLOR	.....	Red,black,white,blue,green...
	绝缘外径 INSULATION DIAMETER	mm	3.51±0.10
屏蔽隔离 SHIELDING	包带 COVERING	.....	/
	屏蔽方式 SCREEN MODE	.....	/
	构造规格 SECTIONAL AREA	AWG/ mm	/
	屏蔽材质 MATERIAL	.....	/
	绞合总外径 TOTAL DIAMETER	mm	/
外被 JACKET	材质 MATERIAL	.....	/
	平均厚度 THE AVERAGE THICKNESS	mm	/
	最小厚度 MINIMUM GAUGE	mm	/
	颜色 COLOR	.....	/
	线材外径 OVERALL DIAMETER	mm	/

印字内容 PRINTING CONTENT

结构简图 STRUCTURE DIAGRAM

绝缘 INSULATION

导体 CONDUCTOR

绝缘 INSULATION

