




胜牌电线规格书

WIRE SPECIFICATION

规格型号 SPEC NO.	UL3239 20AWG	参照标准 REFERENCE STANDARD	UL1581/758
额定温度 RATED TEMPERATURE	150°C	额定电压 RATED VOLTAGE	40KV-DC
阻燃等级 FLAME RETARDANT GRADE	FT2	环保标准 ENVIRONMENTAL STANDARDS	RoHS

结构项目 CONSTRUCTION			
ITEM			
导体 CONDUCTOR	构造规格 SECTIONAL AREA	AWG/ mm	21/0.178±0.008TS
	导体材质 MATERIAL	Tinned copper
	截面积 SECTIONAL AREA	mm ²	0.52
	绞合外径 STRANDED DIAMETER	mm	0.94
绝缘 INSULATION	材质 MATERIAL	Silicone
	平均厚度 THE AVERAGE THICKNESS	mm	1.98
	最小厚度 MINIMUM GAUGE	mm	1.78
	颜色 COLOR	Red,black...
	绝缘外径 INSULATION DIAMETER	mm	4.91±0.10
屏蔽隔离 SHIELDING	包带 COVERING	/
	屏蔽方式 SCREEN MODE	/
	构造规格 SECTIONAL AREA	AWG/ mm	/
	屏蔽材质 MATERIAL	/
	绞合总外径 TOTAL DIAMETER	mm	/
外被 JACKET	材质 MATERIAL	/
	平均厚度 THE AVERAGE THICKNESS	mm	/
	最小厚度 MINIMUM GAUGE	mm	/
	颜色 COLOR	/
	线材外径 OVERALL DIAMETER	mm	/
印字内容 PRINTING CONTENT		*	
<p>结构简图 STRUCTURE DIAGRAM</p> <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <p>绝缘 INSULATION</p>  </div> <div style="text-align: center;"> <p>导体 CONDUCTOR</p>  </div> <div style="text-align: center;"> <p>绝缘 INSULATION</p>  </div> </div>			